

Mixer Feeder

25 Series

Durability · Performance · Design · Craftsmanship · Service



Nobody builds a mixer feeder like the industry leader.

Proven Design

- Discharge door is located at bottom center of mixer feeder.
- Designed to provide the most uniform blend of expensive feed commodities possible, from start to finish

Increases Efficiency

- Provides the most uniform consistency by using 100% of the mixing chamber
- Chute and gate powered by an engine mounted hydraulic system.
- Four counter rotating augers to assure a healthy, high quality feed ration

Reduces Repair Costs

- All construction is heavy-duty and designed for ease of service

Customize with optional equipment

- Discharge conveyor-manual or hydraulic variable height control
- Drag chain or auger conveyor
- Available as truck mounted, trailer mounted or stationary units
- Hydrostatic Drive
- Omni Feed Gate indicator



P.O. Box 544 · Brush, CO 80723 · (970) 842-5161 · Toll Free (800) 523-2614

www.mixerfeeders.com

Mixer Feeder - 25 Series

Model-	4025	4525	5025	5525
Inside Width	92"	92"	92"	92"
Inside Length	144"	168"	192"	192"
Inside Height	64"	64"	64"	72"
Outside Width	94"	94"	94"	94"
Outside Length	162"	186"	210"	210"
Outside Height	77"	77"	77"	85"
Door Opening	39" x 25"	39" x 25"	39" x 25"	39" x 25"
Height on 40" Truck Frame	116"	116"	116"	124"
Height on Trailer	107"	107"	107"	115"
Weight w/Standard Equipment	9700	10500	12150	12500
Augers-				
Standard Flighting Diameter	24"	24"	24"	24"
Flighting Thickness, Top & Bottom	1/2"	1/2"	1/2"	1/2"
Flighting Pitch	3/4p	3/4p	3/4p	3/4p
Pipe Size, Top/Bottom	6" Sch 40/80	6" Sch 40/80	6" Sch 40/80	8" Sch 40/80
Drives-				
Top Augers	RC-100	RC-100	RC-100	RC-100
Bottom Augers	RC-120	RC-120	RC-120	RC-120
Top Auger Shafts	2 7/16"	2 7/16"	2 7/16"	2 7/16"
Bottom Auger Shafts	3 7/16"	3 7/16"	3 7/16"	3 7/16"
Bearings/Bottom Auger Bearings	Self-Aligning, Auger Bearings Mounted Outside of Mixing Chamber/Double-Spherical			
GR-1600 Gear Box	1 3/4" In-Put Shaft, Two 2 5/8" 4140 Heat Treated Out-Put Shafts			
Hydraulic Systems-				
Chute & Gate	Live Power, Engine Mounted, Joy Stick Controlled, Electric Solenoid Valves			
Material-				
Bottom & Lower Sides	1/4" with Replaceable 7 ga Liners (7/16" total thickness)			
Upper Sides & Upper End Panels	10 ga	10 ga	10 ga	10 ga
Lower End Panels & Discharge Bottom	7 ga	7 ga	7 ga	7 ga
Discharge-				
42" Wide Chain -Standard Equip.	58" Long, Optional 12" Extension Available			
Quad Auger-Optional	4-10" Hex Shaft Mounted Augers, 58" Long, Optional 12" Extension Available			
Discharge Drive	PTO Powered Hydraulic System, Poly-Chain Belt Driven, Electric Controlled			
Mixing Time-	Three to Seven Minutes			



MMI Holdings

P.O. Box 544 · Brush, CO 80723 · (970) 842-5161 · Toll Free (800) 523-2614